

DIN rail perforated - NS 15 PERF 2000MM - 1401682

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 5.5 mm, width 15 mm, length: 2000 mm

Product Features

- All DIN rails are also available cut to length
- Particular attention has been paid to high dimensional accuracy and surface tempering
- The design of the DIN rails corresponds to European standard EN 60715



Key commercial data

Packing unit	1 PCE
Minimum order quantity	5 PCE
Catalog page	Page 340 (CL2-2011)
GTIN	 4 017918 020491
Custom tariff number	72166190
Country of origin	GERMANY

Technical data

General data

Height	5 mm
Length	2000 mm
Width	15 mm
Material	Steel
Coating	Galvanized, passivated with a thick layer
Color	silver

DIN rail perforated - NS 15 PERF 2000MM - 1401682

Classifications

ETIM

ETIM 2.0	EC001285
ETIM 3.0	EC001285
ETIM 4.0	EC001285
ETIM 5.0	EC001285

UNSPSC

UNSPSC 11	39121708
UNSPSC 12.01	39121708
UNSPSC 13.2	39121708
UNSPSC 6.01	30212109
UNSPSC 7.0901	39121708

eCl@ss

eCl@ss 4.0	27110804
eCl@ss 4.1	27110804
eCl@ss 5.0	27141143
eCl@ss 5.1	27141143
eCl@ss 6.0	27141143
eCl@ss 7.0	27141143

Drawings

DIN rail perforated - NS 15 PERF 2000MM - 1401682

Dimensioned drawing

