


## Socket - EM-DUO 120/20 - 5600525

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

### Key commercial data

Packing unit	1 PCE
Minimum order quantity	150 PCE
GTIN	 4 046356 688543
Custom tariff number	85366990
Country of origin	UNITED STATES

### Technical data

#### General data

Nominal voltage $U_N$	120 V AC
Nominal current $I_N$	20 A
For country-specific use in	USA
Color	white
Insulating material	PVC 94 V0
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Width	83 mm
Height	134 mm
Depth	49 mm

#### Connection data

Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	6 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	4 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	10
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3

## Socket - EM-DUO 120/20 - 5600525

### Classifications

#### ETIM

ETIM 3.0	EC001325
ETIM 4.0	EC001325
ETIM 5.0	EC001325

#### UNSPSC

UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620
UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610

#### eCl@ss

eCl@ss 4.0	27142305
eCl@ss 4.1	27142305
eCl@ss 5.0	27143412
eCl@ss 5.1	27130801
eCl@ss 6.0	27130803
eCl@ss 7.0	27130803