

SIMATIC ET 200SP, ANALOG OUTPUT MODULE, AQ 4XU/I STANDARD, FITS TO BU-TYPE A0, A1, COLOR CODE CC00, MODULE DIAGNOSIS, 16BIT, +/-0,3%



Product type designation	
General information	
Firmware version	V1.1
usable BaseUnits	BU type A0, A1
Color code for module-specific color identification plate	CC00
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Scalable output range</li> </ul>	No
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated as of version</li> </ul>	V11 SP2 / V13
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated as of version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PCS 7 configurable/integrated as of version</li> </ul>	V8.1 SP1
<ul style="list-style-type: none"> <li>PROFIBUS as of GSD version/GSD revision</li> </ul>	GSD Revision 5
<ul style="list-style-type: none"> <li>PROFINET as of GSD version/GSD revision</li> </ul>	GSDML V2.3
Operating mode	
<ul style="list-style-type: none"> <li>Oversampling</li> </ul>	No

- MSO

No

### CiR - Configuration in RUN

Reparameterization possible in RUN	Yes
Calibration possible in RUN	No

### Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

### Input current

Current consumption, max.	150 mA
---------------------------	--------

### Power loss

Power loss, typ.	1.5 W
------------------	-------

### Address area

#### Address space per module

- Address space per module, max. 8 byte; + 1 byte for QI information

### Analog outputs

Number of analog outputs	4
Voltage output, short-circuit current, max.	45 mA
Cycle time (all channels), min.	5 ms
Analog output with oversampling	No

#### Output ranges, voltage

- 0 to 10 V Yes; 15 bit
- 1 V to 5 V Yes; 13 bit
- -5 V to +5 V Yes; 15 bit incl. sign
- -10 V to +10 V Yes; 16 bit incl. sign

#### Output ranges, current

- 0 to 20 mA Yes; 15 bit
- -20 mA to +20 mA Yes; 16 bit incl. sign
- 4 mA to 20 mA Yes; 14 bit

#### Connection of actuators

- for voltage output two-wire connection Yes
- for voltage output four-wire connection Yes
- for current output two-wire connection Yes

#### Load impedance (in rated range of output)

- with voltage outputs, min. 2 k $\Omega$
- with voltage outputs, capacitive load, max. 1  $\mu$ F
- with current outputs, max. 500  $\Omega$
- with current outputs, inductive load, max. 1 mH

#### Destruction limits against externally applied voltages and currents

• Voltages at the outputs	30 V
<b>Cable length</b>	
• shielded, max.	1 000 m; 200 m for voltage output
<b>Settling time</b>	
• for resistive load	0.1 ms
• for capacitive load	1 ms
• for inductive load	0.5 ms
<b>Errors/accuracies</b>	
Linearity error (relative to output range), (+/-)	0.03 %
Temperature error (relative to output range), (+/-)	0.005 %/K
Crosstalk between the outputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to output area), (+/-)	0.05 %
<b>Operational error limit in overall temperature range</b>	
• Voltage, relative to output area, (+/-)	0.5 %
• Current, relative to output area, (+/-)	0.5 %
<b>Basic error limit (operational limit at 25 °C)</b>	
• Voltage, relative to output area, (+/-)	0.3 %
• Current, relative to output area, (+/-)	0.3 %
<b>Isochronous mode</b>	
Isochronous operation (application synchronized up to terminal)	No
<b>Interrupts/diagnostics/status information</b>	
Substitute values connectable	Yes
<b>Alarms</b>	
• Diagnostic alarm	Yes
<b>Diagnostic messages</b>	
• Diagnostics	Yes
• Monitoring the supply voltage	Yes
• Wire-break	Yes
• Short-circuit	Yes
• Group error	Yes
• Overflow/underflow	Yes
<b>Diagnostics indication LED</b>	
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Channel status display	Yes; Green LED
• for channel diagnostics	No
• for module diagnostics	Yes; green/red DIAG LED
<b>Potential separation</b>	
<b>Potential separation channels</b>	
• between the channels	No

- between the channels and the backplane bus
- between the channels and the supply voltage of the electronics

Yes

Yes

### Permissible potential difference

between different circuits

75 V DC/60 V AC (base isolation)

### Isolation

Isolation tested with

707 V DC (type test)

### Ambient conditions

Ambient temperature during operation

- horizontal installation, min. 0 °C
- horizontal installation, max. 60 °C; Observe derating
- vertical installation, min. 0 °C
- vertical installation, max. 50 °C; Observe derating

### Dimensions

Width

15 mm

### Weights

Weight, approx.

31 g

**last modified:**

29.07.2015