



SIMATIC ET 200SP, Digital output module, DQ 8x 24V DC/0,5A Standard, Source output (PNP,P-switching) Packing unit: 1 piece, fits to BU-type A0, Colour Code CC02, substitute value output, module diagnostics for: short-circuit to L+ and ground, wire break, supply voltage

General information	
Product type designation	DQ 8x24VDC/0.5A ST
HW functional status	From FS02
Firmware version	V0.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	No
usable BaseUnits	BU type A0
Color code for module-specific color identification plate	CC02
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	No
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V14
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	V5.5 SP3 or higher
<ul style="list-style-type: none"> <li>PCS 7 configurable/integrated from version</li> </ul>	V8.1 SP1
<ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>	One GSD file each, Revision 3 and 5 and higher
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	GSDML V2.3
Operating mode	
<ul style="list-style-type: none"> <li>DQ</li> </ul>	Yes
<ul style="list-style-type: none"> <li>DQ with energy-saving function</li> </ul>	No
<ul style="list-style-type: none"> <li>PWM</li> </ul>	No
<ul style="list-style-type: none"> <li>Oversampling</li> </ul>	No
<ul style="list-style-type: none"> <li>MSO</li> </ul>	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	35 mA; without load
output voltage / header	
Rated value (DC)	24 V
Power loss	
Power loss, typ.	1 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>	1 byte; + 1 byte for QI information
Hardware configuration	
Automatic encoding	Yes

<ul style="list-style-type: none"> <li>• Mechanical coding element</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Type of mechanical coding element</li> </ul>	Type A
<b>Selection of BaseUnit for connection variants</b>	
<ul style="list-style-type: none"> <li>• 1-wire connection</li> </ul>	BU type A0
<ul style="list-style-type: none"> <li>• 2-wire connection</li> </ul>	BU type A0
<ul style="list-style-type: none"> <li>• 3-wire connection</li> </ul>	BU type A0 with AUX terminals or potential distributor module
<ul style="list-style-type: none"> <li>• 4-wire connection</li> </ul>	BU type A0 + Potential distributor module
<b>Digital outputs</b>	
Type of digital output	Source output (PNP, current-sourcing)
Number of digital outputs	8
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes
<ul style="list-style-type: none"> <li>• Response threshold, typ.</li> </ul>	1 A
Limitation of inductive shutdown voltage to	Typ. L+ (-50 V)
Controlling a digital input	Yes
<b>Switching capacity of the outputs</b>	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> </ul>	0.5 A
<ul style="list-style-type: none"> <li>• on lamp load, max.</li> </ul>	5 W
<b>Load resistance range</b>	
<ul style="list-style-type: none"> <li>• lower limit</li> </ul>	48 Ω
<ul style="list-style-type: none"> <li>• upper limit</li> </ul>	12 kΩ
<b>Output voltage</b>	
<ul style="list-style-type: none"> <li>• for signal "1", min.</li> </ul>	L+ (-0.8 V)
<b>Output current</b>	
<ul style="list-style-type: none"> <li>• for signal "1" rated value</li> </ul>	0.5 A
<ul style="list-style-type: none"> <li>• for signal "1" permissible range, max.</li> </ul>	0.5 A
<ul style="list-style-type: none"> <li>• for signal "0" residual current, max.</li> </ul>	0.1 mA
<b>Output delay with resistive load</b>	
<ul style="list-style-type: none"> <li>• "0" to "1", max.</li> </ul>	50 μs; at rated load
<ul style="list-style-type: none"> <li>• "1" to "0", max.</li> </ul>	100 μs; at rated load
<b>Parallel switching of two outputs</b>	
<ul style="list-style-type: none"> <li>• for uprating</li> </ul>	No
<ul style="list-style-type: none"> <li>• for redundant control of a load</li> </ul>	Yes
<b>Switching frequency</b>	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> </ul>	100 Hz
<ul style="list-style-type: none"> <li>• with inductive load, max.</li> </ul>	2 Hz
<ul style="list-style-type: none"> <li>• on lamp load, max.</li> </ul>	10 Hz
<b>Total current of the outputs</b>	
<ul style="list-style-type: none"> <li>• Current per channel, max.</li> </ul>	0.5 A
<ul style="list-style-type: none"> <li>• Current per module, max.</li> </ul>	4 A
<b>Total current of the outputs (per module)</b>	
horizontal installation	
<ul style="list-style-type: none"> <li>— up to 60 °C, max.</li> </ul>	4 A
vertical installation	
<ul style="list-style-type: none"> <li>— up to 50 °C, max.</li> </ul>	4 A
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	1 000 m
<ul style="list-style-type: none"> <li>• unshielded, max.</li> </ul>	600 m
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
Substitute values connectable	Yes
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>• Diagnostic alarm</li> </ul>	Yes
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>• Monitoring the supply voltage</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Wire-break</li> </ul>	Yes; Module-wise
<ul style="list-style-type: none"> <li>• Short-circuit to M</li> </ul>	Yes; Module-wise
<ul style="list-style-type: none"> <li>• Short-circuit to L+</li> </ul>	Yes; Module-wise
<ul style="list-style-type: none"> <li>• Group error</li> </ul>	Yes

<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>Monitoring of the supply voltage (PWR-LED)</li> </ul>	Yes; green PWR LED
<ul style="list-style-type: none"> <li>Channel status display</li> </ul>	Yes; green LED
<ul style="list-style-type: none"> <li>for channel diagnostics</li> </ul>	No
<ul style="list-style-type: none"> <li>for module diagnostics</li> </ul>	Yes; green/red DIAG LED
<b>Potential separation</b>	
<b>Potential separation channels</b>	
<ul style="list-style-type: none"> <li>between the channels</li> </ul>	No
<ul style="list-style-type: none"> <li>between the channels and backplane bus</li> </ul>	Yes
<ul style="list-style-type: none"> <li>between the channels and the power supply of the electronics</li> </ul>	No
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Standards, approvals, certificates</b>	
Suitable for safety functions	No
Suitable for safety-related tripping of standard modules	Yes; see FAQ Entry ID: 39198632
<b>Highest safety class achievable in safety mode</b>	
<ul style="list-style-type: none"> <li>Performance level according to ISO 13849-1</li> </ul>	PL d
<ul style="list-style-type: none"> <li>SIL acc. to IEC 61508</li> </ul>	SIL 2
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> </ul>	-30 °C; < 0 °C as of FS02
<ul style="list-style-type: none"> <li>horizontal installation, max.</li> </ul>	60 °C
<ul style="list-style-type: none"> <li>vertical installation, min.</li> </ul>	-30 °C; < 0 °C as of FS02
<ul style="list-style-type: none"> <li>vertical installation, max.</li> </ul>	50 °C
<b>Altitude during operation relating to sea level</b>	
<ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> </ul>	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
<b>Dimensions</b>	
Width	15 mm
Height	73 mm
Depth	58 mm
<b>Weights</b>	
Weight, approx.	30 g
<b>last modified:</b>	9/27/2021 